


# MC255 power amplifier

- Give your home theater the power it deserves with the MC255 5-Channel Home Theater Power Amplifier.
- Highlighted by our new eye-catching TripleView™ Power Output Meter that independently indicates the real time power reading of the three front channels.
- Delivers 250 Watts per channel when using just the three front channels. When using all 5 channels, each receive a healthy 200 Watts per channel.
- Dynamic Power Manager® (DPM) technology delivers the full 200 or 250 Watts to either 4 or 8 Ohm speakers.
- Dynamic headroom - a key feature in a home theater amplifier - has more than doubled from 1.7dB to 3.6dB compared to previous model.
- Features four McIntosh Monogrammed Heatsinks™ that efficiently and silently cool the amplifier; as a result, noisy cooling fans are not needed. A quiet, specially wound toroidal isolation power transformer also helps keep noise to a minimum.
- Can be used to power a 5-channel home theater; can be paired with either our MI128 or MI254 digital amplifiers in home theaters that have additional speakers; or can be used in a two zone configuration with the three front channels used at 250 WPC in one zone and the two surround sound channels used at 200 WPC in a second audio zone.
- Includes Power Guard®, Sentry Monitor™, Power Control, our eco-friendly power management system, and direct LED lighting of the front panel.



The Power Your Home Theater Deserves

**McIntosh®**

LEGENDARY PERFORMANCE®

[www.mcintoshlabs.com](http://www.mcintoshlabs.com)

# MC255 power amplifier

## Power Output:

3 Front Channels only: 250W @ 4 or 8 Ohms  
All 5 Channels: 200W @ 4 or 8 Ohms

## Total Harmonic Distortion:

0.005% maximum from 20Hz to 20kHz

## Signal to Noise Ratio:

108dB

## Dynamic Headroom:

3.6dB

## Damping Factor:

Greater than 70 @ 4 Ohms  
Greater than 140 @ 8 Ohms

## Frequency Response:

+0, -0.25dB from 20Hz to 20kHz  
+0, -3.0dB from 10Hz to 100kHz

## Inputs & Outputs:

5 Balanced inputs  
5 Unbalanced inputs  
Gold-plated speaker binding posts

## Overall Dimensions (W x H x D):

17-1/2" (44.45cm) x 9-7/16" (23.97cm)  
x 21" (53.3cm)

## Weight:

89.5 lbs (40.6kg) net,  
122.5 lbs (55.6kg) in shipping carton

## For the Consumer's Protection:

In order to ensure the highest level of customer satisfaction, new McIntosh products may only be purchased from an Authorized McIntosh Dealer; and, with certain limited exceptions may only be purchased over-the-counter or delivered and installed by the Authorized McIntosh Dealer. McIntosh does not warrant, in any way, products that are purchased from anyone who is not an Authorized McIntosh Dealer, or that have had their serial numbers altered or defaced.



## Companion Products

The MX170 and MX123 A/V Processors, MI128 and MI254 Power Amplifiers, MVP901 Blu-ray Player, XRT1.1K or XR100 Floorstanding Speakers, LCR80 Center Channel Speaker, WS500 or WS300 In-Wall Speakers, CS200 In-Ceiling Speaker and MPC1500 Power Conditioner are logical companions for the MC255 Power Amplifier. Your Authorized Dealer can provide additional information on other McIntosh product combinations.

To learn more, please call us at 1.800.538.6576.

# McIntosh®

LEGENDARY PERFORMANCE®

[www.mcintoshlabs.com](http://www.mcintoshlabs.com)